

# CHECK VALVES & FOOT VALVES

9 - 7 - 11

**DEAN BENNETT SUPPLY CO**  
**TOLL FREE : 800-621-4291**  
**PRICES ARE YOUR NET COSTS**

Page 25

## BRASS CHECK VALVES

Spring loaded check valves will operate in either the vertical or horizontal position and are designed to provide secure sealing action under both high and low pressure applications. Below check valves are rated at 400 psi. Heavy cast-brass body with hex ends are built with extra strength for your deep well installations. Corrosion resistant poppet, jam proof Delrin stem guide, and stainless steel spring ensure a watertight seal each and every time. Below check valves are female pipe thread x female pipe thread. 1", 1-1/4" & 2" are LEAD FREE

1/2"	5BCV	\$ 18.60	1-1/4"	12BCV	\$ 36.25	2-1/2"	25BCV	\$ 263.00
3/4"	7BCV	\$ 19.00	1-1/2"	15BCV	\$ 38.50	3"	30BCV	\$ 317.00
1"	10BCV	\$ 26.50	2"	20BCV	\$ 82.00	4"	40BCV	\$ 544.00

We have a full selection of Stainless Steel Check Valves

## 2-HOLE BRASS CHECK VALVES

Heavy brass bodied check valves with two tappings - - a 1/4" female pipe thread tapping on the outlet side of the check poppet and a 1/8" female pipe thread tapping on the inlet side of the check poppet. These check valves are female pipe thread x female pipe thread.

3/4"	7B2HCV	\$ 33.25	1-1/4"	12B2HCV	\$ 40.60	2"	20B2HCV	\$ 79.50
1"	10B2HCV	\$ 31.00	1-1/2"	15B2HCV	\$ 55.25			

## SPECIALTY SUBMERSIBLE CHECK VALVES

\$ 24.00 12M10FBCV **1-1/4" M x 1" F BRASS CHECK VALVE** 1-1/4" male pipe thread x 1" female pipe thread check valve that fits directly into pump discharge.

\$ 60.00 20M20FBCV **2" M x 2" F BRASS CHECK VALVE** Same design as above.

\$ 22.25 10DICV **1" DUCTILE IRON CHECK VALVE** Female x female iron pipe thread.

\$ 32.00 12DICV **1-1/4" DUCTILE IRON CHECK VALVE** Female x female iron pipe thread.

\$ 99.25 20DICV **2" DUCTILE IRON CHECK VALVE** Female x female iron pipe thread.

\$ 292.00 30DICV **3" DUCTILE IRON CHECK VALVE** Female x female iron pipe thread.

\$ 457.00 40DICV **4" DUCTILE IRON CHECK VALVE** Female x female iron pipe thread.

1" - 3" Ductile Iron rated 400 PSI and 4" - 8" Ductile Iron rated 600 PSI

## BRASS FOOT VALVES

These foot valves have a red brass casting with a machined exterior and are rated at 200 psi. A tapered stainless steel strainer screen and bottom cap offers the ultimate in a non-corrosive foot valve. A stainless steel spring and a brass poppet with neoprene O-ring seal ensure a leak-proof foot valve for all your jet and centrifugal pumps.

1/2"	5BFV	\$ 7.50	1-1/4"	12BFV	\$ 18.00	3"	30BFV	\$ 148.00
3/4"	7BFV	\$ 8.70	1-1/2"	15BFV	\$ 23.90	4"	40BFV	\$ 267.00
1"	10BFV	\$ 13.25	2"	20BFV	\$ 40.50			

## BRASS SWING CHECK VALVES

These valves are normally installed in a horizontal position and are not spring loaded. Brass body valves with female pipe thread connection are rated 125 psi. Brass swing disc seats directly against a ground brass valve seat.

1"	10BSCV	\$ 16.00	1-1/2"	15BSCV	\$ 32.75
1-1/4"	12BSCV	\$ 25.25	2"	20BSCV	\$ 49.00

## SPECIALTY FOOT VALVES AND STRAINERS

\$ 53.25 20CIFV **2" CAST IRON FOOT VALVE** has a painted red finish with a 2" female iron pipe thread. Includes a weighted neoprene flapper check to maintain you pump's prime.

\$ 115.00 30CIFV **3" CAST IRON FOOT VALVE** like above but 3" female iron pipe thread.

\$ 15.95 20FS **2" FLAT STRAINER ONLY** Zinc plated steel construction with 3/8" round holes. Has a 2" female pipe thread top connection.

\$ 22.75 30FS **3" FLAT STRAINER ONLY** like above unit except 3" female iron pipe thread.

**QUALIFIES FOR OUR \$1,000.00 FREIGHT PREPAID POLICY**  
**MANY FITTINGS ARE ALSO AVAILABLE IN STAINLESS STEEL**